



Rundstål

Skaldrejet

Blanktrukket

Centerlesslebet



Skaldrejet



Lagerlængde: 5-6 m. EN 1.4305, dog 2,5-3 m. Max. vægt pr. længde 1500 kg

4

D mm	Tolerance mm	kg/m	EN 1.4301/ 1.4307	EN 1.4404	EN 1.4305	SS 2324/ EN 1.4460	EN 1.4462	EN 1.4057
20,0	-0/+0,21	2,5					•	
22,0	-0/+0,21	3,0	•	•				
25,0	-0/+0,21	3,9	•	•	•		•	•
26,0	-0/+0,21	4,2		•				
28,0	-0/+0,21	4,8	•	•	•			
30,0	-0/+0,21	5,5	•	•	•		•	•
31,0	+0/ -0,25	5,9				•		
32,0	-0/+0,25	6,3	•	•	•			
35,0	-0/+0,25	7,6	•	•	•		•	•
36,0	+0/ -0,25	8,0	•			•		
38,0	-0/+0,25	8,9	•	•	•			
40,0	-0/+0,25	9,9	•	•	•		•	•
41,0	+0/ -0,25	10,4				•		
42,0	-0/+0,25	10,9	•	•	•			
45,0	-0/+0,25	12,5	•	•	•		•	
46,0	+0/ -0,25	13,1				•		
50,0	-0/+0,25	15,4	•	•	•		•	
51,2	+0/ -0,30	16,2				•		
55,0	-0/+0,30	18,7	•	•	•		•	•
56,2	+0/ -0,30	19,5				•		
60,0	-0/+0,30	22,2	•	•	•		•	
61,2	+0/ -0,30	23,1				•		
65,0	-0/+0,30	26,1	•	•	•		•	
66,2	+0/ -0,30	27,0				•		
70,0	-0/+0,30	30,2	•	•	•		•	•
71,4	+0/ -0,30	31,4				•		
75,0	-0/+0,30	34,7	•	•	•		•	
80,0	-0/+0,30	39,5	•	•	•		•	
81,4	+0/ -0,35	40,8				•		
85,0	-0/+0,35	44,6	•	•	•		•	
90,0	-0/+0,35	49,9	•	•	•		•	
91,4	+0/ -0,35	51,5				•		
95,0	-0/+0,35	55,6	•	•	•		•	
100,0	-0/+0,35	61,7	•	•	•		•	
105,0	-0/+1,00	68,0	•	•				
107,0	+0/ -0,35	70,6				•		
110,0	-0/+1,00	74,6	•	•	•			
115,0	-0/+1,00	81,5	•	•	•			
120,0	-0/+1,00	88,8	•	•	•		•	
125,0	-0/+1,00	96,3	•	•				
130,0	-0/+1,00	104,2	•	•			•	
135,0	-0/+1,00	112,4	•	•	•			
140,0	-0/+1,00	120,8	•	•	•		•	
145,0	-0/+1,00	129,6	•	•	•			
150,0	-0/+1,00	138,7	•	•			•	
155,0	-0/+1,00	148,1	•	•				
160,0	-0/+1,00	157,8	•	•				
165,0	-0/+1,00	167,9	•	•	•			

• = lagerdimension

Fortsættes side 5



Skaldrejet

Lagerlængde: 5-6 m. EN 1.4305 dog 2,5-3 m. Max. vægt pr. længde 1500 kg

D mm	Tolerance mm	kg/m	EN 1.4301/ 1.4307	EN 1.4404	EN 1.4305	SS 2324/ EN 1.4460	EN 1.4462
170,0	-0/+1,0	178,2	•	•			•
175,0	-0/+1,0	188,8		•			
180,0	-0/+1,0	200,0	•	•	•		•
185,0	-0/+1,0	211,0		•			•
190,0	-0/+1,0	223,0	•	•			•
200,0	-0/+1,0	247,0	•	•			
210,0	-0/+2,0	272,0	•	•			•
220,0	-0/+2,0	298,0	•	•			
225,0	-0/+2,0	312,0	•	•			
230,0	-0/+2,0	326,0	•	•			
240,0	-0/+2,0	355,0	•	•			
250,0	-0/+2,0	386,0	•	•			•
255,0	-0/+2,0	401,0		•			
260,0	-0/+2,0	417,0	•	•			
270,0	-0/+2,0	450,0	•	•			
275,0	-0/+2,0	466,0	•				•
280,0	-0/+2,0	484,0	•	•			
285,0	-0/+2,0	501,0	•	•			
300,0	-0/+2,0	555,0	•	•			•
310,0	-0/+2,0	593,0	•				
320,0	-0/+2,0	631,0	•	•			
325,0	-0/+2,0	651,0	•	•			•
340,0	-0/+2,0	713,0	•				
350,0	-0/+2,0	755,0	•	•			
360,0	-0/+2,0	799,0	•				
375,0	-0/+2,0	867,0	•	•			
400,0	-0/+2,0	987,0	•	•			
450,0	-0/+2,0	1249,0	•	•			
500,0	-0/+2,0	1541,0	•	•			

• = lagerdimension

INOX
SAVE - SERVICE
 Vores moderne båndsave kan:
 Diameter: 10 - 500 mm
 Tolerancer: ± 0,25 mm
 Snitkanal: 1,5 mm
Få et tilbud!



Blanktrukket

Lagerlængde: 3-6 m. EN 1.4305 dog 2,5-3 m.

D mm	kg/m	EN 1.4301/1.4307	EN 1.4404	EN 1.4305
		trukket h9	trukket h9	trukket h9
3,00	0,06	●	●	
4,00	0,10	●	●	
5,00	0,15	●	●	●
6,00	0,22	●	●	●
7,00	0,30	●	●	●
8,00	0,40	●	●	●
9,00	0,50	●	●	●
10,00	0,62	●	●	●
11,00	0,75	●	●	
12,00	0,89	●	●	●
13,00	1,04	●		●
14,00	1,21	●	●	●
15,00	1,39	●	●	●
16,00	1,58	●	●	●
17,00	1,78	●	●	●
18,00	2,00	●	●	●
19,00	2,23	●	●	●
20,00	2,47	●	●	●
22,00	2,98	●	●	●
24,00	3,55	●	●	●
25,00	3,85	●	●	●

● = lagerdimension



Gevindstænger

ISO 3506-1. Lagerlængder 1000 mm

Dimension	kg/m	A2 / AISI 304	A4 / AISI 316L
		tol. g6	tol. g6
M 5	0,124	●	●
M 6	0,177	●	●
M 8	0,319	●	●
M10	0,500	●	●
M12	0,725	●	●
M14	0,970	○	○
M16	1,330	●	●
M18	1,650	○	○
M20	2,080	●	●
M22	2,540	●	●
M24	3,000	●	○
M30	4,750	○	○
M36	6,900	○	○

● = lagerdimension ○ = værkslager

Fra værkslager kan vi levere længder på 2000, 3000 og 4000 mm

Vi kan levere UNC-størrelser fra værk

Er dit behov specielt ?

Har du specielle behov, der falder udenfor standard lagervarer?

Hvad enten det drejer sig om speciel kvalitet eller speciel dimension, så er smedet udførelse det oplagte valg.

Læs mere om mulighederne på side 12.



Centerlesslebet

Lagerlængde: 3-6 m. EN 1.4305 dog 2,5-3 m.

INOX

7

D mm	kg/m	EN 1.4301 / 1.4307 slebet		EN 1.4404 slebet		EN 1.4305 slebet			EN 1.4460 slebet
		h9	h8	h9	h8	h9	h8	h7	h9
4,00	0,10						•		
5,00	0,15						•		
6,00	0,22	•					•		
8,00	0,40	•		•			•		
10,00	0,62	•	•	•		•	•		
12,00	0,89	•	•	•	•	•	•		
14,00	1,21	•		•		•	•		
15,00	1,39	•	•		•	•	•		
16,00	1,58	•	•	•	•	•	•		
17,00	1,78						•		
18,00	2,00	•		•		•	•		
20,00	2,47	•	•	•	•	•	•	•	•
22,00	2,98	•		•			•		
24,00	3,55			•		•			
25,00	3,85	•	•	•	•	•	•	•	•
26,00	4,17	•				•			
28,00	4,83	•		•		•			
30,00	5,55	•	•	•	•	•	•	•	•
32,00	6,31	•		•		•			
35,00	7,55	•	•	•		•			
36,00	7,99	•		•		•			
38,00	8,90	•		•		•			
40,00	9,87	•	•	•		•	•		
45,00	12,50	•	•	•		•			
50,00	15,40	•	•	•		•			•
55,00	18,70	•		•		•			
60,00	22,20	•		•		•			•
65,00	26,10	•		•		•			
70,00	30,20	•		•					
75,00	34,70	•		•					
80,00	39,50	•		•					
90,00	49,90	•		•					
100,00	61,70	•		•					

• = lagerdimension

Er dit behov specielt ?

Har du behov for specialprofiler ? Du kan læse om vores mange muligheder på side 12

